

# TRIO PVC



### APPLICABLE

- In public and residential buildings
- In heated, inhabited rooms
- In roof pitch range of 15°-90°
- Suitable on all common roofings with proper flashing

### FEATURES

- Centre pivot u-PVC roof window
- Triple glazing
- Toughened outer glass
- Excellent insulation
- High humidity resistance
- Maintenance free PVC profile
- Elegant bottom handle
- Two passive ventilation positions via handle
- Double gasket system between frame and sash
- Double Low-e coating
- Easy installation
- 10 year guarantee

### MATERIAL

- Lead free PVC
- Steel reinforcement
- Polystyrene insulation insertion

### COVER PARTS

- Aluminium, lacquered, grey colour (RAL 7043)

### HANDLE

- Ergonomically designed moulded zinc handle, lacquered

### HINGE

- Pivot hinge

CE



### APY B1500

PANE	
Construction	4-12-3HS-12-3H
Thickness of glazing (mm)	34
Low E	■ ■
Gas	Argon
Toughened	■
U <sub>g</sub> (W/m²K)	0.8
Total solar energy transmittance	0.55
WINDOW	
U <sub>w</sub> (W/m²K)	1.1
Water tightness	E1500
Air permeability	Class 3
Resistance to wind load	Class C3
Sound reduction	33 (-1,-3) dB
COLOUR	
White	■

### MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m²
C2A	55 × 78 cm	55 cm	77,8 cm	39,8 cm	64,9 cm	37,3 cm	59 cm	0.220
C4A	55 × 98 cm	55 cm	97,8 cm	39,8 cm	84,9 cm	37,3 cm	79 cm	0.295
F4A*	66 × 98 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
F6A	66 × 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
M4A	78 × 98 cm	78 cm	97,8 cm	62,8 cm	84,9 cm	60,3 cm	79 cm	0.476
M6A	78 × 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597
M8A	78 × 140 cm	78 cm	139,8 cm	62,8 cm	126,9 cm	60,3 cm	121 cm	0.729
M10A*	78 × 160 cm	78 cm	159,8 cm	62,8 cm	146,9 cm	60,3 cm	141 cm	0.850
P6A*	94 × 118cm	94 cm	117,8 cm	78,8 cm	104,9 cm	76,3 cm	99 cm	0,755
P8A*	94 × 140cm	94 cm	139,8 cm	78,8 cm	126,9 cm	76,3 cm	121 cm	0,925
S6A	114 × 118 cm	114 cm	117,8 cm	98,8 cm	104,9 cm	96,3 cm	99 cm	0.953

\* Only TFX and UFX flashings are available

### FLASHING RANGE FOR DIFFERENT ROOFING MATERIALS\*\*



LSX

**SLATE**  
Suitable for slates and flat roofing, up to 8mm (max overall thickness is 16 mm)



TFX

**TILE**  
Suitable for low profile tiles and profiled materials between 16-50 mm



FTX

**INTERLOCKING FLAT TILE**  
Suitable for interlocking flat tiles between 16 and 50 mm.



UFX

**UNIVERSAL**  
Suitable for high profiled tiles and profiled materials between 16-120 mm



SSX

**STANDING SEAM**  
Suitable for standing seam steel sheet coverings

\*\* Combi solutions are also available, please contact your dealer for details.

### BLIND RANGE\*




DUA

BLACKOUT



MIA

AWNING



SSR

ROLLER SHUTTER



\*For the right product code of blinds, please take the type of blind, size of RW and colour code, e.g. DUA C2A 4219